



Kontrol Kube

This task must only be performed by trained personnel

Edited by: Melissa Dzwonek	Approved by: M - Bruce Hancock W - Willie Anseeuw W - Todd Jackson	Created by: M - Bruce Hancock W - Willie Anseeuw W - Todd Jackson	Date created / last revision date: C - March 2012 (EHSO) R - November 26, 2015
--------------------------------------	--	---	---

Hazards Present: <ul style="list-style-type: none"> Exposure to asbestos-containing materials Ladder use 	Personal Protective Equipment (PPE) or Devices Required: PPE: <ul style="list-style-type: none"> Gloves Half-face respirator with P100 filters Tyvek suit with foot covers Additional PPE for work task Equipment: <ul style="list-style-type: none"> Asbestos work box (see "Asbestos Equipment Box Contents List") Kontrol Kube user manual 	Additional Training Requirements: <ul style="list-style-type: none"> Job-specific training Asbestos awareness training Asbestos decontamination procedures HEPA vac procedures
---	---	---

Safe Work Procedure:

- Whenever possible, this work task should be performed with two people: one to work in the Kontrol Kube and one to stand by/assist from outside.
- As per the Asbestos Work Permit, determine whether HVAC system shutdown is required.
- If HVAC shutdown is required, arrange for the system to be locked out by Central Energy Plant. Ensure lockout procedures are complete before starting the work.
- Don all required PPE.
- Roll Kontrol Kube into desired position and erect as per drawings in user manual.
- Extend Kontrol Kube upward until it is 2" from the ceiling.
- Establish negative pressure by connecting HEPA vacuum to the hose port.
- Select the tools and materials you will need, including a water spray bottle and rags, before entering the Kube.
- Perform required work task, following applicable Safe Job Procedures.
- Use the HEPA vacuum to remove any visible debris inside the Kontrol Kube, then thoroughly wipe all interior surfaces with water and a rag.
- Once the inner walls are wiped down, clean your coveralls with the HEPA vacuum or wet rag. Discard and package used coveralls and rags in 6 mil "asbestos" labelled poly bags. Twist the neck of each poly bag and secure with tape, then fold down and secure with tape. Place this bag into a second poly bag, and seal in the same manner (double bag).
- Dismantle the Kontrol Kube using the reverse steps for set up.
- Use wash bucket to wash hands and respirator.
- Drop off waste bags at an approved location for disposal pickup.
- If at any time throughout the above steps you believe that asbestos exposure may have occurred, initiate decontamination procedures immediately by suspending all activities that may further disturb the material, and contacting your supervisor.



Additional notes:

Supervisor

It is the responsibility of the Supervisor to ensure:

- All employees know, understand and comply with the safe job procedure.
- The safe work procedure is reviewed annually and amended, if required.
- Any changes that have been made to the safe job procedure must be immediately communicated to all employees. This includes a posted bulletin and verbal notification.

Employees

It is the responsibility of the Employee to:

- Read, understand and comply with the safe job procedure.

REPORT ANY HAZARDOUS SITUATION TO YOUR SUPERVISOR IMMEDIATELY

Remember - you and any other worker have the Right to Refuse Dangerous Work!

Applicable Legislation & Guidance Documents	
<p>Guidance Documents:</p> <ul style="list-style-type: none"> • Manitoba Workplace Safety and Health Act W210, • Manitoba Workplace Safety and Health Regulation 217/2006 	<p>This Safe Work Procedure will be reviewed any time the task, equipment, or materials change and at a minimum every three years or when circumstances change.</p>

EMPLOYEE SIGNATURE: Jedd Jackson

EMPLOYEE SIGNATURE: [Signature]

MANAGEMENT SIGNATURE: [Signature]

REVIEWED BY PPLASH yes / no DATE: _____